Before Beginning

- Read all instructions completely.
- Wear protective gloves, glasses, long sleeves, and nose/face mask to avoid contact with human waste.
- For hygenic reasons, rinse tank and hose thoroughly.

Instructions

- 1. Pull old lanyard from tank body.
- Turn old Level Gauge clockwise until two finger tabs line up with "O"s on tank body. Lift off old Level Gauge. Discard.
- 3. Line up and insert new Level Gauge into tank. Turn counterclockwise until finger tabs line up with "V"s on tank.
- 4. Connect lanyard on tank.

THETF®RD

40531

Holding Tank Accessories

Part No.

SmartTote[®] AutoStop™ Level Gauge Kit

Made in U.S.A.

Thetford Corporation Ann Arbor, MI 48106 • 1-800-521-3032 • www.thetford.com

Form #40620 2//07

Before Beginning

- Read all instructions completely.
- Wear protective gloves, glasses, long sleeves, and nose/face mask to avoid contact with human waste.
- For hygenic reasons, rinse tank and hose thoroughly.

Instructions

- 1. Pull old lanyard from tank body.
- Turn old Level Gauge clockwise until two finger tabs line up with "O"s on tank body. Lift off old Level Gauge. Discard.
- 3. Line up and insert new Level Gauge into tank. Turn counterclockwise until finger tabs line up with "V"s on tank.
- 4. Connect lanyard on tank.



Form #40620 2/07